PRIVACY & DECORATIVE FILM Fine Acid Etch – Bronze BR-912

Opalux[®] translucent privacy screening films are used to give two-way privacy without seriously reducing the natural light level. These films have a finely textured matt finish, and are applied to new or existing glass.

The Opalux® Fine Acid Etch Bronze is a specialist frosted film still provides two-way privacy however it has a unique bronze appearance to it. For both new build and refurbishment projects, Opalux® privacy screening films offer a cost effective and flexible alternative to traditional acid-etching, sandblasting or printing. This product allows freedom in the initial glass specification, with privacy being allocated later, when and where it is required, quickly and easily applied on site without removing the glass. As well as adding a distinctive designer style to your office interior, this allows some through-vision for reception areas and meeting rooms, where total screening is not required, but a degree of privacy and a high light transmission are desirable.

FEATURES

- High light transmission
- Quick, retro-fit installation
- Removable
- Incorporate manifestations and graphics

BENEFITS

- Two-way privacy whilst maintaining abundant light levels
- Introduce privacy when and where it is required; ideal for glazing in rooms with a change of use
- Gives the option to remove, replace or update in the future
- Can be used to help satisfy Health & Safety requirements for large areas of uninterrupted glazing, such as glass partitions

PERFORMANCE	E DATA	BR-912
SOLAR ENERGY	Transmitted	48%
	Reflected	15%
	Absorbed	37%
VISIBLE LIGHT	Transmitted	31%
	Reflected (Interior)	12%
	Reflected (Exterior)	12%
UV Rejection		99%
Glare Reduction		65%
Shading Coefficient		0.67
Solar Heat Gain Coefficient (G-Value)		0.58
U-Value (W/m²K)		5.63
Total Solar Energy Rejected		42%
Product Warranty		10 years

PHYSICAL PROPERTIES

Material	PET
Liner	Silicone Coated PET
Structure	Single Ply
Adhesive Type	Acrylic
Suitable for plotter-cutting graphics	No

NOTES

Test results are produced from film applied to 3mm clear single glass. Performance data is subject to change without prior notice. Accurate selection of window film requires specialist knowledge, and it is recommended that specifiers contact the company at the specification stage. It is the users' responsibility to ensure the product is suitable for the intended use. The seller shall not be liable for any direct, indirect or consequential loss or damage howsoever arising.

SPECIFICATION

The privacy window film is to be Opalux® BR-912, as manufactured by Opalux® (www.opaluxwindowfilms.com). The film is to be installed to the interior surface of the glass, and the unique product roll numbers used are to be registered in accordance with the manufacturer's warranty procedure.

OPALUX WINDOW FILM TECHNOLOGY WWW.OPALUXWINDOWFILMS.COM