



01

# 01 SOLAR CONTROL FILM

## Internal Application Dual-Reflective Neutral 25 SO-25DR-iSR

Opalux® Dual-Reflective Neutral 25 offers superior one-way privacy effects than conventional reflective silver films. This is of particular use in combating solar heat gain whilst offering a lower internal reflection.

| PERFORMANCE DATA                      |                      | SO-25DR-iSR |
|---------------------------------------|----------------------|-------------|
| SOLAR ENERGY                          | Transmitted          | 21%         |
|                                       | Reflected            | 36%         |
|                                       | Absorbed             | 43%         |
| VISIBLE LIGHT                         | Transmitted          | 24%         |
|                                       | Reflected - Interior | 18%         |
|                                       | Reflected - Exterior | 38%         |
| UV Rejection                          |                      | 99%         |
| Glare Reduction                       |                      | 73%         |
| Shading Coefficient                   |                      | 0.38        |
| Solar Heat Gain Coefficient (G-Value) |                      | 0.33        |
| U-Value (W/m2k)                       |                      | 5.84        |
| Total Solar Energy Rejected           |                      | 67%         |
| Product Warranty                      |                      | 10 Years    |

DOWNLOAD THE FULL DATA SHEET AT  
[WWW.OPALUXWINDOWFILMS.COM](http://WWW.OPALUXWINDOWFILMS.COM)