## Opalux® TRADE Privacy & Decorative Film

Blackout Removable - Internal

Code: TPA-01BKO-iRM



Opalux® TRADE Removable Blackout films are used to provide blackout and give two-way 24-hr privacy, particularly when required on a temporary basis. This film has a satin black finish and can be applied to most new or existing glass.

The Opalux TRADE Removable Blackout is a quick and easy solution for installations where all daylight and vision through needs to be controlled and will be applied to the glass on a short term basis.

It removes cleanly with no adhesive if removed within 6 months of installation. This product has been successfully

used where black is required and vision through needs to be prevented due to reasons such as temporary building work, office refurbishment or studio creation.

This removable blackout film offers 24-hr privacy and blocks out all daylight or artificial light through the window or lightbox, and is totally opaque.

Features	Benefits
Easily Removable	Cleanly removable within 6 months of installation leaving no or very little adhesive residue
Virtully 0% light transmission	Prevents all light transmission and vision through the glass both ways, increasing security and privacy $% \left( 1\right) =\left( 1\right) \left( 1\right$
Quick, Retro-fit installation	Introduce blackout and privacy when and where it is required; ideal for glazing in rooms with a temporary change of use $$
Screening of harmful UV rays	Reduces the premature fading of interior furnishings
Maximum Glare Reduction	Alleviate the discomfort caused by excessive glare

Performance Data		
Total Solar Energy		
Transmitted	1%	
Reflected	7%	
Absorbed	92%	
Visible Light		
Transmitted	<1%	
Reflected	7%	
Ultra-Violet Rejected	<99%	
Shading Coefficient	0.36	
Total Solar Energy Rejected	70%	

## Specification:

The privacy & decorative window film is to be Opalux® TPA-01BKO-iRM, as manufactured by Opalux® (www.opalux.co.uk). The film is to be installed to the interior surface of the glass, and the unique product roll numbers used are to be registered in accordance with the manufacturer's warranty procedure.

Physical Properties		
Material	P€T	
liner	Silicone Coated PET	
Structure	N/A	
Adhesive Type	Removable Pressure Sensitive	
Product Removability	Within 6 months of installation	

## Notes:

Test results are produced from film applied to clear glass. Performance data is subject to change without prior notice. Accurate selection of window films requires specialist knowledge, and it is recommended that specifiers contact the company at the specification stage. Please refer to the Opalux® TRADE Product Warranty form for the full terms and conditions of the Opalux® TRADE limited warranty. It is the users' responsibility to ensure the product is suitable for the intended use. The seller shall not be liable for any direct or consequential loss howsoever arising.