



## TRANSPARENT COLOUR TINTED FILMS

Opalux® Art colours window films applied to clear glass are optically clear and transparent. They give designers a versatile option for contributing to the atmosphere of a place by tinting the windows from a wide selection of colours.

Classrooms, children's wards, entrances, porticos, exhibition displays, museums, stage sets, public buildings, restaurants, gyms, sports centres are some examples where creative designs can add to the overall theme or mood to be projected.

The Opalux® Art Colours are a brilliant way to give a striking effect to any glass. These tinted films are a great decorative film as they maintain the optical clarity.

Where appropriate you will be connected to an Opalux® approved dealer who can discuss your requirements, visit site if necessary, and provide costings for the film installation.



Accurate selection of window films requires specialist knowledge, and it is recommended that specifiers contact the company at the specification stage +44 (0)845 026 1125 or email [solutions@opaluxwindowfilms.com](mailto:solutions@opaluxwindowfilms.com)

PRIVACY & DECORATIVE

# TRANSPARENT COLOUR TINTED FILMS



PRIVACY & DECORATIVE

## Art Light Blue

PERFORMANCE DATA		DE-14ALBL-ISR
SOLAR ENERGY	Transmitted	N/A
	Reflected	N/A
	Absorbed	31%
VISIBLE LIGHT	Transmitted	44%
	Reflected (Interior)	N/A
	Reflected (Exterior)	N/A
UV Rejection		95%
Glare Reduction		50%
Shading Coefficient		N/A
Solar Heat Gain Coefficient (G-Value)		N/A
U-Value (W/m <sup>2</sup> K)		N/A
Total Solar Energy Rejected		N/A
Product Warranty		5 years

## Art Blue

PERFORMANCE DATA		DE-16ALBL-ISR
SOLAR ENERGY	Transmitted	N/A
	Reflected	N/A
	Absorbed	32%
VISIBLE LIGHT	Transmitted	20%
	Reflected (Interior)	N/A
	Reflected (Exterior)	N/A
UV Rejection		95%
Glare Reduction		77%
Shading Coefficient		N/A
Solar Heat Gain Coefficient (G-Value)		N/A
U-Value (W/m <sup>2</sup> K)		N/A
Total Solar Energy Rejected		N/A
Product Warranty		5 years

## Art Dark Blue

PERFORMANCE DATA		DE-21ADBL-ISR
SOLAR ENERGY	Transmitted	N/A
	Reflected	N/A
	Absorbed	35%
VISIBLE LIGHT	Transmitted	10%
	Reflected (Interior)	N/A
	Reflected (Exterior)	N/A
UV Rejection		95%
Glare Reduction		89%
Shading Coefficient		N/A
Solar Heat Gain Coefficient (G-Value)		N/A
U-Value (W/m <sup>2</sup> K)		N/A
Total Solar Energy Rejected		N/A
Product Warranty		5 years

## Art Lilac

PERFORMANCE DATA		DE-23ALI-ISR
SOLAR ENERGY	Transmitted	N/A
	Reflected	N/A
	Absorbed	29%
VISIBLE LIGHT	Transmitted	37%
	Reflected (Interior)	N/A
	Reflected (Exterior)	N/A
UV Rejection		95%
Glare Reduction		58%
Shading Coefficient		N/A
Solar Heat Gain Coefficient (G-Value)		N/A
U-Value (W/m <sup>2</sup> K)		N/A
Total Solar Energy Rejected		N/A
Product Warranty		5 years

## Art Purple

PERFORMANCE DATA		DE-23APU-ISR
SOLAR ENERGY	Transmitted	N/A
	Reflected	N/A
	Absorbed	34%
VISIBLE LIGHT	Transmitted	11%
	Reflected (Interior)	N/A
	Reflected (Exterior)	N/A
UV Rejection		95%
Glare Reduction		88%
Shading Coefficient		N/A
Solar Heat Gain Coefficient (G-Value)		N/A
U-Value (W/m <sup>2</sup> K)		N/A
Total Solar Energy Rejected		N/A
Product Warranty		5 years

## Art Green

PERFORMANCE DATA		DE-34AGN-ISR
SOLAR ENERGY	Transmitted	N/A
	Reflected	N/A
	Absorbed	40%
VISIBLE LIGHT	Transmitted	40%
	Reflected (Interior)	N/A
	Reflected (Exterior)	N/A
UV Rejection		95%
Glare Reduction		55%
Shading Coefficient		N/A
Solar Heat Gain Coefficient (G-Value)		N/A
U-Value (W/m <sup>2</sup> K)		N/A
Total Solar Energy Rejected		N/A
Product Warranty		5 years

## TRANSPARENT COLOUR TINTED FILMS CONTINUED



### Art Light Green

PERFORMANCE DATA		DE-36ALGN-ISR
SOLAR ENERGY	Transmitted	N/A
	Reflected	N/A
	Absorbed	32%
VISIBLE LIGHT	Transmitted	54%
	Reflected (Interior)	N/A
	Reflected (Exterior)	N/A
UV Rejection		95%
Glare Reduction		39%
Shading Coefficient		N/A
Solar Heat Gain Coefficient (G-Value)		N/A
U-Value (W/m <sup>2</sup> K)		N/A
Total Solar Energy Rejected		N/A
Product Warranty		5 years

### Art Pink

PERFORMANCE DATA		DE-38API-ISR
SOLAR ENERGY	Transmitted	N/A
	Reflected	N/A
	Absorbed	27%
VISIBLE LIGHT	Transmitted	35%
	Reflected (Interior)	N/A
	Reflected (Exterior)	N/A
UV Rejection		95%
Glare Reduction		60%
Shading Coefficient		N/A
Solar Heat Gain Coefficient (G-Value)		N/A
U-Value (W/m <sup>2</sup> K)		N/A
Total Solar Energy Rejected		N/A
Product Warranty		5 years

### Art Light Pink

PERFORMANCE DATA		DE-39ALPI-ISR
SOLAR ENERGY	Transmitted	N/A
	Reflected	N/A
	Absorbed	19%
VISIBLE LIGHT	Transmitted	41%
	Reflected (Interior)	N/A
	Reflected (Exterior)	N/A
UV Rejection		95%
Glare Reduction		53%
Shading Coefficient		N/A
Solar Heat Gain Coefficient (G-Value)		N/A
U-Value (W/m <sup>2</sup> K)		N/A
Total Solar Energy Rejected		N/A
Product Warranty		5 years

### Art Red Violet

PERFORMANCE DATA		DE-41ARDV-ISR
SOLAR ENERGY	Transmitted	N/A
	Reflected	N/A
	Absorbed	42%
VISIBLE LIGHT	Transmitted	10%
	Reflected (Interior)	N/A
	Reflected (Exterior)	N/A
UV Rejection		95%
Glare Reduction		89%
Shading Coefficient		N/A
Solar Heat Gain Coefficient (G-Value)		N/A
U-Value (W/m <sup>2</sup> K)		N/A
Total Solar Energy Rejected		N/A
Product Warranty		5 years

### Art Red

PERFORMANCE DATA		DE-43ARD-ISR
SOLAR ENERGY	Transmitted	N/A
	Reflected	N/A
	Absorbed	30%
VISIBLE LIGHT	Transmitted	18%
	Reflected (Interior)	N/A
	Reflected (Exterior)	N/A
UV Rejection		95%
Glare Reduction		80%
Shading Coefficient		N/A
Solar Heat Gain Coefficient (G-Value)		N/A
U-Value (W/m <sup>2</sup> K)		N/A
Total Solar Energy Rejected		N/A
Product Warranty		5 years

### Art Light Red

PERFORMANCE DATA		DE-45ALRD-ISR
SOLAR ENERGY	Transmitted	N/A
	Reflected	N/A
	Absorbed	26%
VISIBLE LIGHT	Transmitted	25%
	Reflected (Interior)	N/A
	Reflected (Exterior)	N/A
UV Rejection		95%
Glare Reduction		72%
Shading Coefficient		N/A
Solar Heat Gain Coefficient (G-Value)		N/A
U-Value (W/m <sup>2</sup> K)		N/A
Total Solar Energy Rejected		N/A
Product Warranty		5 years



## TRANSPARENT COLOUR TINTED FILMS CONTINUED

### Art Orange

PERFORMANCE DATA		DE-48AOR-ISR
SOLAR ENERGY	Transmitted	N/A
	Reflected	N/A
	Absorbed	25%
VISIBLE LIGHT	Transmitted	39%
	Reflected (Interior)	N/A
	Reflected (Exterior)	N/A
UV Rejection		95%
Glare Reduction		56%
Shading Coefficient		N/A
Solar Heat Gain Coefficient (G-Value)		N/A
U-Value (W/m <sup>2</sup> K)		N/A
Total Solar Energy Rejected		N/A
Product Warranty		5 years

### Art Yellow

PERFORMANCE DATA		DE-53AYE-ISR
SOLAR ENERGY	Transmitted	N/A
	Reflected	N/A
	Absorbed	15%
VISIBLE LIGHT	Transmitted	78%
	Reflected (Interior)	N/A
	Reflected (Exterior)	N/A
UV Rejection		95%
Glare Reduction		11%
Shading Coefficient		N/A
Solar Heat Gain Coefficient (G-Value)		N/A
U-Value (W/m <sup>2</sup> K)		N/A
Total Solar Energy Rejected		N/A
Product Warranty		5 years

PRIVACY & DECORATIVE